

	1	2	3	4	5	6	7	8																												
	GP Level	GP3S						REV.	ECN NO.																											
F																																				
E																																				
D																																				
C	<p>1. RACK MOUNTED ALUMINUM CHASSIS, BLACK MEDIUM TEXTURE 1524 mm LENGTH 55 mm WIDTH 65 mm DEPTH (OUTLET SECTION) 113 mm DEPTH (BREAKER SECTION)</p> <p>2. INPUT: 200-240V 16A 1-PHASE, 50/60 Hz CABLE: 3m LENGTH</p> <p>3. OUTPUT: 200-240V, 50/60 Hz 10A AT 20 IEC C13 RECEPTACLES (A1~A8, A11~A12, B1~B2, B5~B12) 16A AT 4 IEC C19 RECEPTACLES (A9~A10, B3~B4)</p> <p>4. BREAKERS: NONE</p> <p>5. CURRENT METER : LOCAL & GUI DISPLAY ACCESSIBLE VIA ETHERNET (RJ45 PORT) INTERFACES: WEB (HTTP) SNMP SMTP (E-MAIL NOTIFICATION) ACCURACY: 1.5% FROM 0.4A TO 2A AND 1% FROM 2A TO 10A RESOLUTION: <10A : ±0.001A ≥10A : ±0.01A RANGE: 0.4A~10A</p>		<p>6. TEMPERATURE AND HUMIDITY SENSORS (EMP001): TEMPERATURE: ONE FOR INTERNAL AND THE OTHER FOR EXTERNAL MEASUREMENT ACCESSIBLE VIA ETHERNET (RJ45 PORT) RANGE: 0°C TO 65°C HUMIDITY: ONE FOR EXTERNAL MEASUREMENT ACCESSIBLE VIA ETHERNET (RJ45 PORT) RANGE: 20% TO 90%</p> <p>7. OUTLET LED INDICATOR : ON: OUTLET IS POWERED OFF: OUTLET IS UNPOWERED BLINKING: CRITICAL ALARM</p> <p>8. OPTIONAL KITS: KIT1: EMP001 (744-A1576-00P) KIT2: KBLT01(744-A1419-00P)</p> <p>9. SPARE PARTS: PART1: SPK001(744-A1418-00P) PART2: SPK003(744-A1582-00P) PART3: SPK002(744-A1581-00P)</p>						<p>PART1</p> <p>PART2 (IEC309,C20)</p> <p>PART3 (C19,C20)</p> <p>KIT1</p> <p>KIT2</p>																											
B	<p>10. RoHS COMPLICANT PER DIRECTIVE 2011/65/EC WITH APPLICABLE EXEMPTIONS REACH COMPLIANCE</p> <p>11. GW: 6.54KG NW: 4.91KG</p>																																			
A	<table border="1"> <tr> <td>TITLE</td> <td colspan="2">EATON ePDU OUTLINE DRAWING</td> <td>DRAW</td> <td></td> </tr> <tr> <td>CATALOG NO.</td> <td colspan="2">eMAA12</td> <td>DESIGN</td> <td></td> </tr> <tr> <td>MANUF No.</td> <td>9001-22065</td> <td rowspan="2"></td> <td>CHECKED</td> <td></td> </tr> <tr> <td>COATING</td> <td>POWDER COATING</td> <td>SAFETY</td> <td></td> </tr> <tr> <td>UNITS</td> <td>mm</td> <td rowspan="2">A4</td> <td>APPROVED</td> <td></td> </tr> <tr> <td>SHEET</td> <td>1/1</td> <td>SCALE</td> <td>1:1</td> </tr> </table>						TITLE	EATON ePDU OUTLINE DRAWING		DRAW		CATALOG NO.	eMAA12		DESIGN		MANUF No.	9001-22065		CHECKED		COATING	POWDER COATING	SAFETY		UNITS	mm	A4	APPROVED		SHEET	1/1	SCALE	1:1		
TITLE	EATON ePDU OUTLINE DRAWING		DRAW																																	
CATALOG NO.	eMAA12		DESIGN																																	
MANUF No.	9001-22065		CHECKED																																	
COATING	POWDER COATING		SAFETY																																	
UNITS	mm	A4	APPROVED																																	
SHEET	1/1		SCALE	1:1																																
	TC-RDW-49-19 REV B	2	3	4	5	6	7	MECHANICAL																												